

# DL-854N28B | E series

4MP IR Motorized Dome Network Camera



- 1/3" 4MP CMOS
- H.265 Dual-stream Encoding
- IR Effective Range 20~30m
- High Quality Motorized Lens 2.8~12mm
- IVA (Smart Function) Supported
- Multiple Web Browser Supported, IE/Safari/Chrome/Firefox
- P2P Cloud Function By Mobile App (AntarView Pro)
- Lightning Protection Up to 6KV
- IP67 Ingress Protection
- Built-in PoE



## System Overview

E series 4MP IP cameras are cost-efficient solution which powered by H.265 and embedded face detection algorithm. It delivers crystal clear images and supports industry-leading IVA smart event alarm. Cloud function is built-in for every device, which is more convenient and flexible for real-time and remote viewing.

## Functions

### H.265

Delivering high quality video with up to 70% bandwidth saving. H.265 is the evolutionary optimization of traditional H.264. The H.265 includes a series of encoding strategy such as Dynamic ROI-smart 2D&3D noise reduction.

### IVA (Intelligent Video Analysis)

It allows detection on multiple object behaviors, such as Tripwire, Intrusion, Objects Detection and Target Counting etc.

### Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank.

Supports  $\pm 30\%$  input voltage tolerance, it could work safely in extreme unstable power condition.

With working temperature range  $-30^{\circ}\text{C}$  to  $+60^{\circ}\text{C}$ , it works well in a variety of harsh outdoor environments.

## Technical Parameters

### Camera

Model	DL-854N28B	Flash/DDR	16MB/256MB
Image Sensor	1/3" 4MP CMOS	S/N Ratio	More than 52dB
Min. Illumination	0.08Lux/F1.4 (color) 0 Lux with IR on	IR Distance	20~30m
Effective Pixels	2592(H)*1520(V)	IR LED No.	4

### Lens

Focal Length	Motorized 2.8~12mm	FOV	37°~100°
Aperture	F1.4		

### Video

Compression	H.265 / H.264	WDR	120dB
Resolution	4MP(2592*1520 / 2560*1440 / 2048*1520)/ 1080(1920*1080)1.3MP(1280*960)/720P(1280*720) D1(720*576)/VGA(620*480)/CIF(352*288)	Day/Night	Auto(ICR)/Color/B/W
Bit Rate Control	CBR/VBR	White Balance	Supported
Bit Rate	116Kbps-32Mbps	Defog	Supported
Streaming	Dual stream	Noise Reduction	3D DNR
Frame Rate	Main stream : 2592*1520(1~25/30fps) Sub stream : 720*576(1~25/30fps)	Mirror	Supported
Digital Zoom	12x	Flip	Supported
Audio Compression	G.711u	BLC	Supported
		ROI	Support 4 fixed region for main stream and sub stream separately
		Anti-flicker	Supported
		Privacy Mask	4 Areas

### Alarm & Audio

Video Detection	Motion Detection, Video Shelter	IVA	Face Detection/Tripwire/Intrusion/ Abandon/Missing/ Target Counting/ Video Shelter
Audio	1 channel audio input, 1 channel audio output optional		

### Network

Ethernet	1 RJ-45 port(10/100Mbps)	Web Browsers	IE/Firefox/Chrome/Safari
Protocols	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPoE, UPNP, SMTP, SNMP	VMS	AntarVis 2.0
Onvif	Onvif Profile S	Mobile App	AntarView Pro
Max. Online Users	4	Platform	Mac OS/ Windows/iOS/Android


### General

Working Temperature	-30°C~+60°C	Ingress Protection	IP67
Working Humidity	10~90%	Dimensions	Φ102*93.2mm
Power Supply	PoE, IEEE802.3af DC12V±10%	Net Weight	0.50KG
Power Consumption	< 3W	Gross Weight	0.70KG

### Ordering Information

Type	Part Number	Description
4MP Camera	DL-854N28B	4MP Network Camera(2.8~12mm Lens)

### Dimensions (mm)



[www.zkteco.com](http://www.zkteco.com)

