

ES-35J11/12J | P series

5MP IR Eyeball Analog Camera



- · 1/2.5" 5MP COMS
- · AHD/TVI/CVI/CVBS Video Output
- · IR Effective Range 10~20m
- · High Quality Optical Lens 2.8mm/3.6mm Optional







System Overview

P series HD analog camera adopts advanced 4-in-1 ISP and 1/2.5" image sensor, featured by the excellent image details with wide FOV. It offers built-in UTC function to switch the signal output flexibly among the 4 popular formats. It's ideal solution for SMB solution with high cost-performance ratio and simple installation.

Functions

Long Distance Transmission

Powered by leading HD Videoloss technology, it supports up to 500m/800m transmission through RG59/RG6 coaxial cables respectively.

Smart IR

P series is designed with smart IR function to avoid IR LED overexposure when object/people is getting closer to the camera in the night, ensuring the light intensity is changing proportionally with the distance between camera and objects.

Advanced 4-in-1 Technology

P series is built-in with advanced 4-in-1 technology, it's equipped with UTC chipset on board which could support to adjust HD analog signal output flexibly, such as AHD/TVI/CVI/CVBS. It's the final solution for true plug-n-play to work with any brand of HD analog DVR seamlessly.

Protection

Support ±30% input voltage tolerance, it could work safely in extremely unstable power condition.

With working temperature range from -30°C to +60 °C, it works well in a variety of harsh outdoor environments.

Technical Parameters

Camera

Model	ES-35J11J	ES-35J12J	Effective
Image Sensor	1/2.5"5MP COMS		S/N Ratio
Scanning System	Progressive		IR Distan
Min. Illumination	0.01Lux/F 0 Lux w	2.0(color) ith IR on	IR LED No

Effective Pixels	2592(H)*1944(V)
CALD .:	
S/N Ratio	More than 52dB
IR Distance	10~20m
IR LED No.	1

Lens

Focal Length	2.8mm	3.6mm
Aperture	F2.0	

FOV	89°	85°
-----	-----	-----

Video

Video Output	AHD/TVI/CVI/CVBS
Resolution	20fps@5MP
OSD Menu	Supported
BLC	Supported
WDR	120dB

Defog	Supported
AGC	Supported
Day/Night	Auto(ICR)/Manual
White Balance	Supported
Noise Reduction	2D/3D DNR

General

Working Temperature	-30°C~+60°C
Working Humidity	10~90%
Power Supply	DC12V±10%
Power Consumption	<3.2W(IR cut off)

Ingress Protection	N/A
Dimensions	Ф92 * 78mm
Net Weight	0.15KG
Gross Weight	0.2KG

Ordering Information

	Type	Part Number	Description
5MP Camera	ES-35J11J	5MP Analog Camera(2.8mm Lens)	
	Sivii Cumera	ES-35J12J	5MP Analog Camera(3.6mm Lens)

Dimensions (mm)







