

KIT-8604NE-4F/4-BS852O12B | Facial NVR KIT series

4-Channel 4MP Facial NVR with 4 x 2MP Network Cameras



ZKTeco Facial Security System provides all the components to quickly install, configure, and employ a complete facial video surveillance solution. The IP cameras offer the clarity of 2MP video and face detection function, and the NVR offers built-in face recognition algorithms that can be used on multiple advanced applications, such as face access control, face attendance check and gate system.

Key Features

NVR Model: Z8604NE-4F

- Max. 4 ch Face Recognition with Face Capture cameras
- Support up to 20,000 face templates
- Support Blacklist/Whitelist alarm linkage actions
- Friendly and intuitive GUI(Graphic User Interface)
- Support mobile phone monitoring (iOS / Android)



Camera Model: BS-852O12B

- 2MP High definition image output
- Embedded Face Detection Algorithm
- Maximum IR Length 20m with Smart IR
- IP67 Environmental Protection



Specifications

BioFace Lite NVR

Model	Z8604NE-4F
Face Recognition Channel	4 Channel
Face Templates	20,000 pictures
Face Library	Black List/White List/Other
Video Compression	H.265+/H.265/H.264
Recording Resolution	4MP/3MP/1080p/960p/720p
Max. Decoding	4MP@25fps/30fp
Record Mode	Manual/External Alarm/Motion/ Scheduled/IVA Alarm"
Playback	1/4
Search Mode	IVA Search/Time/Motion Detection
Intelligent Function	Target Counting, Object Abandon/Missing, Intrusion, Tripwire, Video Shelter, Scene change

Display	1* HDMI (1080P)
Max. HDD	1 SATA, Up to 8TB/Bay
Audio I/O	1/1
Alarm I/O	4/4
USB	2*USB 2.0
Network Port	1 RJ-45 Port(10 /100MMbps)
Power Supply	DC 12V/2A
Consumption	Max. 10W without HDD
Demension	255mm*210mm*43mm
Working Enviroment	0°C~+55°C; 10~90%

Face Detection Camera

Model	BS 852O12B
Image Sensor	1/3" 2MP CMOS
Minimum Illumination	0.01Lux/F2.0 (Color) 0 Lux with IR on
Eective Pixels	1920(H)* 1080(V)
IR Distance	20m
Focal Length	3.6mm
Angle of View	92°
Compression	H.265/H.264
Frame Rate	25/30fps@2MP

WDR	DWDR
Day/Night	Auto ICR
Intelligent Function	Face Detection/Tripwire/Intrusion/Object Left/Missing/Target Counting/Video Shelter
Power Supply	DC12V±10%; PoE, IEEE802.3af
Power Consumption	<3W
Casing	Metal
Protection	IP67
Working Environment	30°C 60°C; 0% 90%
Dimensions	145*65*65mm

Standard Package


NVR	1* Z8604NE-4F
Camera	4* BS-852O12B
Accessory	Defaults to no accessories. Cable and HDD optional
Package Dimensions	363*183*270.7mm
Package Weight	4.5KG

Ordering Information


Type	Part Number	Accessories Options
Facial NVR KIT	KIT-8604NE-4F/ 4-BS852O12B	Standard
		2* 18m Cat5+ Cable & 2*30m Cat5+ Cable
		1TB WD HDD
		4* Cables+ 1TB WD HDD

Dimensions (mm)

Z8604NE-4F



BS 852O12B



www.zkteco.com

