



Mars Pro-S1200 Series

Mars Pro-S1200 Dual-Lane Speed Gate Mars Pro-S1211 Dual-Lane Speed Gate (w/ controller and RFID reader)

Mars Pro-S1222 Dual-Lane Speed Gate (w/ controller and fingerprint & RFID readers)















Highly Durable and Low Maintenance Costs

- Modularized structure design
- Exposed mounting holes for easy installation
- Mainly made of SPCC (option: SUS316 stainless steel)

PGIC Controller

- · Equipped with a PGIC controller
- Access control
- General features and parameters settings on the controller's menu

LED Indicator

- Visual cues for correct walking direction
- Clear guidance with green and red illustration

Switchable Reader Panel

- Four panels available:
 - RFID only
 - RFID & Fingerprint
 - RFID & QR Code
 - RFID & Fingerprint & QR Code
- Reducing middlemen's inventory pressure
- Reducing installation time & expenses

Installation Place for Facial Recognition **A&C Terminals**

- Diameter: 34mm
- Integration with Facial Recognition, Temperature and Mask Detection **Terminals**

Infrared Sensors

20 pairs of infrared sensors for stronger tailgating detection

Servo Motor

- Faster opening speed
- Much more guiet
- Higher durability










Specifications

Model	Mars Pro - S1200 Series
Power Requirements	AC100V to 120V / 200V to 240V, 50 to 60Hz
Working Power	70W; 20W (stand-by)
Drive Unit	Servo Motor
MCBF	10 millions
Technical Throughput Rate	Up to 30 people per minute
Barrier Movement	Swing
Noise	<60dB
Infrared Sensor	20 pairs
LED Indicator	Support
Working Temperature	-25℃ to 65℃
Working Humidity	20% to 95% (non-condensing)
Working Environment	Indoor / Outdoor (if sheltered)
Lane Width	650mm (option: ≤900mm)
Dimensions (L*W*H)	1360 * 120 * 1020 (mm)
Dimensions with Packaging (L*W*H)	1510 * 365 * 1216 (mm)
Net Weight	65kg (±5kg)
Gross Weight	90kg (±5kg)
Cabinet Material	SPCC (option: SUS316 stainless steel)
Lid Material	SPCC (option: SUS316 stainless steel)
Dimensions with Packaging (L*W*H) Net Weight Gross Weight Cabinet Material Lid Material Barrier Material Packing Material	Acrylic (option: glass)
Packing Material	Wooden case
Protection Level	IP34

Applications



Dimensions (mm)





V3.0 2021.05.21