

Z516/32/64NHR

16/32/64 Channel 4K&H.265+ Network Video Recorder



Features

- H.265+/H.265/H.264+/H.264 Decoding
- Support 16/32/64CH 4K Resolution Preview and Playback
- Support HDMI up to 4K output
- DHCP, FTP, DNS, DDNS, NTP, UPNP, RTSP etc.
- ONVIF Profile S Compatible
- Cloud Service, P2P
- Mobile phone remote monitoring (iOS, Android)
- Multi-browser access (IE, Chrome, Firefox, Safari)



System Overview

ZKTeco Z500NHR series could deliver up to 4K resolution excellent image over advanced H.265+ decoding.

It's the ideal consideration for the balance of quality, performance and budget.

The friendly GUI provides intuitive shortcut operations, remote control and management, flexible storage, smart search and playback.

It's widely used for the government, banking sectors, manufacturers, educational or commercial projects.

Powered by the strong interoperability and Onvif Profile S, it's compatible with plenty of 3rd party IPC or crossing platform VMS.

Functions

Up to 4K (3840 x 2160) Resolution Preview or Playback

IVA (Intelligent Video Analysis) supported, it allows to detect multiple object behaviors, like tripwire, intrusion, objects missing or abandoned etc.

Smart Add

Only one click to add all the private IP cameras into NVR like analog system connection, to avoid IP conflict problem.

AntarView

Flexibly and remotely monitor at anytime or anywhere with AntarView APP.

Technical Parameters

Model	Z516NHR	Z532NHR	Z564NHR
System			
Processor	Multi-core Embedded Processor		
Operation System	Embedded Linux		
Display			
Interface	2 HDMI, 1 VGA		
OSD	Camera Title, Time, Video Loss, Camera lock, Motion Detection, Recording		

Video Detection and Alarm

Linkaged Events	Alarm out, Linkage Record, Snapshot, PTZ Linkage, Tour, Show Message, Buzzer, Send Email, FTP, Upload Cloud, Push Alarm
Motion Detection	MD Zones: 396 (22x18)
Alarm Input	16 channel Input
Alarm Output	4 channel Output

Playback and Backup

Playback Channel	16	32
Search Mode	Time/Date, MD and Exact Search, Smart Search	
Playback Function	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Next Camera, Previous Camera, Full Screen, Shuffle, Backup Selection, Digital Zoom	
Backup Mode	USB device/Network	

Interface and Storage

Network Interface	2 RJ-45 port (10/100Mbps)
HDD	8 SATA, up to 10TB capacity for each HDD
USB	3xUSB 2.0

Audio and Video

IPC Input Channel	16	32	64
Two-way Talk	1 Channel Input, 1 Channel Output, RCA		

Recording

Video Compression	H.265+/H.265/H.264+/H.264		
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1.3MP/720P etc.		
Incoming Bandwidth	128Mbps	200Mbps	256Mbps
Bitrate	Self-adaptive with IP Camera		
Record Mode	Manual, Schedule, Motion Detection, Video Loss, Privacy Mask, VQD, IVA		

Network

PoE	N/A		
Network Protocol	HTTP, TCP/IP, IPV4, UDP, RTSP, DHCP, FTP, PPPOE, NTP, UPnP, P2P, DDNS, SMTP		
Max. Online User	20		
Mobile App	Antarview (iOS & Android)		
Interoperability	Onvif Profile S, SDK		

Electrical

Power supply	110V~220V±10% 47Hz~63Hz
Consumption	20W without HDD

Environmental

Working Temperature	-10℃ ~+55℃
Working Humidity	10~90%

Package

Dimensions	441mmx448mmx88mm
Net Weight	7KG
Gross Weight	9.5KG


Certifications

CF	EN55032, EN55024, EN61000-3-2, EN61000-3-3
FCC	Part 15 Subpart B, ANSI C63.4-2014


Ordering Information

Type	Part Number	Description
Non PoE NVR	Z516NHR	16 channel 8 SATA NVR
	Z532NHR	32 channel 8 SATA NVR
	Z564NHR	64 channel 8 SATA NVR

Dimensions (mm)



Rear Panel



www.zkteco.technology

