

ZKBio610P Series

All-in-One Biometric Smart POS Terminal



Features

- Power-efficient Intel® Celeron J1900 2.0 GHz Quad-Core processor
- 15" Bezel-Free true-flat display with PCAP touch
- Multiple I/O interfaces for peripherals
- Standard with 80mm thermal printer
- Standard with 2G RAM and 32G SSD
- Standard with 8C high-definition digital tube
- Optional 3 tracks MSR, attached VFD&12.1" customer display
- Faster installation and maintainability

Optional



Magnetic Stripe
Card Reader



2nd LCD Display Screen



Barcode Scanner



Mifare/RFID



Thermal Printer



Cash Drawer



VFD Customer Display



Fingerprint

Specifications

Model Name	ZKBio610P	ZKBio630P	ZKBio650P
System			
Processor	Intel® Celeron J1900 Quad-Core Processor (2.0 GHz)	Intel® Core™ i3 Processor(1.7GHz)	Intel® Core™ i5 Processor (1.6 GHz up to 2.6 GHz)
System Memory	2GB Standard, DDR3L 1333MHz (Max.8GB)		
Storage Device	32GB Msata SSD Standard,1*2.5"HDD / 2.5"SSD		
OS Supported	Windows 7, Windows 8, Windows 10 IoT Enterprise, POS Ready 7, Linux		
Audio	Realtek ALC662		
Display and Touch			
Type	15"TFT LCD, LED Backlight		
Resolution	1024x768		
Touch Screen	Five-Wire Analog Resistive or Projected Capacitive		
Customer Display	LED (8C digital tube)		
External I/O Ports			
VGA	1*DB-15		
USB	5*USB2.0,1*USB3.0		
Scerial	1*RS232(Max.4pcs)		
LAN	1*RJ45		
Audio	1*Line-out		
Power			
Power Supply	Adaptor 12V DC 5A		
Physical Environmental			
Operating Temperature	0°C to 35°C at 20% to 80% RH		
Storage Temperature	-20°C to 55°C at 20% to 80% RH		
Packing Dimensions	41.7*28*57(L*W*H)		
Net Weight	11.7kg		
Packing Weight	13.9kg		
Certification	CE, FCC		
Color	Black		
Options & Peripherals			
Second Display	12.1"TFT LCD		
Customer Display(VFD)	VFD (2*20 lines)		
MSR	3 Tracks		
Fingerprint	USB fingerprint reader (SLK20R)		

