

BS-31A11B | EZ series

720P IR Bullet Analog Camera



- · 1/4" 720P CMOS
- · AHD/TVI/CVI Video Output
- · IR Effective Range 10~20m
- · High Quality Optical Lens 2.8mm
- IP67 Ingress Protection









System Overview

EZ Series 720P HD analog camera adopts advanced 3-in-1 ISP and 1/4 image sensor, featured by the excellent image details with wide FOV, and compact design with unique 1-key installation base. It offers built-in UTC function to switch the signal output flexibly among the 3 popular technologies. It's ideal solution for SMB solution with high cost-performance ratio and simple installation.

Functions

Long Distance Transmission

Powered by leading HD Videoloss technology, it supports up to 500m/800m transmission via RG59/RG6 coaxial cables respectively.

Smart IR

EZ series is designed with smart IR function to avoid of the IR LED overexposure when object/people is getting closer to the camera in the night, ensuring the light intensity is changing proportionally with the distance between camera and objects.

Advanced 3-in-1 Technology

EZ series 720P HD analog camera is built-in with advanced 3-in-1 technology, it's equipped with UTC chipset on board which could support to adjust HD analog signal output flexibly, such as AHD/TVI/CVI. It's the final solution for true plug-n-play to work with any brand of HD analog DVR seamlessly.

Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank. Support $\pm 30\%$ input voltage tolerance, it could work safely in extreme unstable power condition. With working temperature ranging from -30°C to +60°C, it works well in a variety of harsh outdoor environments.

Technical Parameters

Camera

Model	BS-31A11B
Image Sensor	1/4" 720P CMOS
Scanning System	Progressive
Min. Illumination	0.1Lux/F2.4 (color) 0 Lux with IR on

Effective Pixels	1280(H)* 720(V)
S/N Ratio	More than 52dB
IR Distance	10~20m
IR LED No.	10

Lens

Focal Length	2.8mm
Aperture	F2.4

FOV 63°	
---------	--

Video

Video Output	AHD/TVI/CVI
Resolution	25/30fps@720P
OSD Menu	Supported
BLC	N/A
WDR	DWDR

AGC		Supported	
Day/Night		Auto(ICR)/Manual	
White Balance	10	Supported	
Noise Reduction		2D DNR	

General

Working Temperature	-30°C~+60°C
Working Humidity	10~90%
Power Supply	DC12V±10%
Power Consumption	<3.2W(IR off)

Dimensions	145 (L)*65 (W)*65(H)mm
Net Weight	0.26KG
Gross Weight	0.37KG

Ordering Information

Туре	Part Number	Description
720P Camera	BS-31A11B	720P Analog Camera(2.8mm Lens)

Dimensions (mm)





