

BS-855L12/13K | EZ series

5MP IR Bullet Network Camera



- 1/2.7" 5MP CMOS
- H.265 Dual-stream Encoding
- IR Effective Range 10~20m
- High Quality Optical Lens 3.6mm/6mm optional
- IVA (Smart Function) Supported
- Multiple Web Browser Supported, IE/Safari/Chrome/Firefox
- P2P Cloud Function By Mobile App (AntarView Pro)
- Lightning Protection Up to 6KV
- IP67 Ingress Protection
- Built-in PoE



System Overview

EZ series 5MP IP cameras are cost-efficient solution which powered by and advanced cutting-edge for video monitoring. It delivers crystal clear images and supports industry-leading IVA smart event alarm.

Cloud function is built-in for every device, which is more convenient and flexible for real-time and remote viewing.

Functions

H.265

Delivering high quality video with up to 70% lower bandwidth. H.265 is the evolutionary optimization of H.264 and traditional H.264. The H.265 includes a series of encoding strategy such as Dynamic ROI and smart 2D&3D noise reduction.

IVA (Intelligent Video Analysis)

It allows detection on multiple object behaviors, such as Tripwire, Intrusion, Objects Detection, Target Counting etc.

Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank.

Supports $\pm 30\%$ input voltage tolerance, it could work safely in extreme unstable power condition.

With working temperature range from -30°C to $+60^{\circ}\text{C}$, it works well in a variety of harsh outdoor environments.

Technical Parameters

Camera

Model	BS-855L12K	BS-855L13K	Flash	16MB
Image Sensor	1/2.7" 5MP CMOS		S/N Ratio	More than 52dB
Min. Illumination	0.03Lux/F2.0 (color) 0 Lux with IR on		IR Distance	10~20m
Effective Pixels	2560(H)* 1920(V)		IR LED No.	1

Lens

Focal Length	3.6mm	6mm	FOV	90.5°	99.6°
Aperture	F2.0				

Video

Compression	H.265/H.264		WDR	DWDR
Resolution	5MP(2560*1920)/1080P(1920*1080)/1.3M(1280*960)/720P(1280*720)/D1(704*576)/CIF(352*288)		Day/Night	Auto(ICR)/Color/B/W
Bit Rate Control	CBR/VBR		White Balance	Supported
Bit Rate	16Kbps-4Mbps		Defog	Supported
Streaming	Dual stream		Noise Reduction	3D DNR
Frame Rate	Main stream: 2560*1920(1~15fps) Sub stream: 704*576(1~25/30fps)		Mirror	Supported
Digital Zoom	12x		Flip	Supported
Audio Compression	G.711u		BLC	N/A
			ROI	N/A
			Anti-flicker	Supported
			Privacy Mask	4 Areas

Alarm & Audio

Video Detection	Motion Detection, Video Shelter	IVA	Tripwire/Intrusion/Abandon/Missing/ Target Counting/ Video Shelter
Audio	N/A		

Network

Ethernet	1 RJ-45 port(10/100Mbps)	Web Browsers	IE/Firefox/Chrome/Safari
Protocols	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP/DNS, DDNS, FTP, NTP, PPPoE, UPNP, SMTP, SNMP	VMS	AntarVis 2.0
Onvif	Onvif Profile S	Mobile App	AntarView Pro
Max. Online Users	2	Platform	Mac OS/ Windows/iOS/Android


General

Working Temperature	-30°C~+60°C	Ingress Protection	IP67
Working Humidity	10~90%	Dimensions	160.3 (L)*63.4 (W)*64.5 (H)mm
Power Supply	PoE, IEEE802.3af DC12V±10%	Net Weight	0.3KG
Power Consumption	<3W	Gross Weight	0.45KG

Ordering Information

Type	Part Number	Description
2MP Camera	BS-855L12K	2MP Network Camera(3.6mm Lens)
	BS-855L13K	2MP Network Camera(6mm Lens)

Dimensions (mm)



www.zkteco.com

