

DL-858M28B | W series

Starlight/WDR 8MP IR Dome Network Camera



- 1/1.8" 8MP STARVIS CMOS
- H.265 Dual-stream Encoding
- IR Effective Range 20~30m
- High Quality Motorized Lens 3.6~11mm
- IVA (Smart Function) Supported
- Multiple Web Browser Supported, IE/Safari/Chrome/Firefox
- P2P Cloud Function By Mobile App (AntarView Pro)
- Lightning Protection Up to 6KV
- IP67 Ingress Protection
- Built-in PoE
- Support Antinot IK10



System Overview

W series 8MP IP cameras are high-end project-oriented solution which is powered by Starlight, true WDR and advanced cutting-edge for video monitoring.

It delivers crystal clear images and supports Industry-leading IVA smart event alarm

Cloud function is built-in for every device, which is more convenient and flexible for real-time and remote viewing.

Functions

H.265

Delivering high quality video with up to 70% lower bandwidth. H.265 is the evolutionary optimization of H.264 and traditional H.264. The H.265 includes a series of encoding strategy such as Dynamic ROI and smart 2D&3D noise reduction.

IVA (Intelligent Video Analysis)

It allows detection on multiple object behaviors, such as Tripwire, Intrusion, Objects Detection, Target Counting etc.

Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank.

Supports $\pm 30\%$ input voltage tolerance, it could work safely in extreme unstable power condition.

With working temperature range from -30°C to $+60^{\circ}\text{C}$, it works well in a variety of harsh outdoor environments.

Technical Parameters

Camera

| | | | |
|-------------------|---|-------------|----------------|
| Model | DL-858M28B | Flash/DDR | 128MB/256MB |
| Image Sensor | 1/1.8" 8MP STARVIS CMOS | S/N Ratio | More than 52dB |
| Min. Illumination | 0.06Lux/F1.5(color) 0 Lux with IR on | IR Distance | 20~30m |
| Effective Pixels | 3840(H)* 2160(V) | IR LED No. | 4 |

Lens

| | | | |
|--------------|--------------------|-----|--------------|
| Focal Length | Motorized 3.6~11mm | FOV | 46.6°~112.5° |
| Aperture | F1.5 | | |

Video

| | | | |
|-------------------|---|-----------------|--|
| Compression | H.265/H.264 | WDR | 120dB |
| Resolution | 8MP(3840*2160)/5MP(2592*1944)3MP(2048*1536)1080P(1920*1080)/ 1.3M(1280*960)/720P(1280*720)/D1(730*576)/VGA(620*480)/CIF(352*288) | Day/Night | Auto(ICR)/Color/B/W |
| Bit Rate Control | CBR/VBR | White Balance | Supported |
| Bit Rate | 16Kbps-20Mbps | Defog | Supported |
| Streaming | Dual stream | Noise Reduction | 3D DNR |
| Frame Rate | Main stream: 3840*2160@15fps Sub stream: 720*576(1~25/30fps) | Mirror | Supported |
| Digital Zoom | 12x | Flip | Supported |
| Audio Compression | G.711u | BLC | Supported |
| | | ROI | Support 4 fixed region for main stream and sub stream separately |
| | | Anti-flicker | Supported |
| | | Privacy Mask | 4 Areas |

Alarm & Audio

| | | | |
|-----------------|--|-----|--|
| Video Detection | Motion Detection, Video Shelter | IVA | Face Detection/Tripwire/Intrusion/Object Left/Missing/Target Counting /Sound Detection/Fire Detection/Scene Change/VQD |
| Audio | 1 channel audio input; 1 channel audio output optional | | |

Network

| | | | |
|-------------------|--|--------------|-----------------------------|
| Ethernet | 1 RJ-45 port(10/100Mbps) | Web Browsers | IE/Firefox/Chrome/Safari |
| Protocols | TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP/DNS, DDNS, FTP, NTP, PPPoE, UPNP, SMTP, SNMP | VMS | AntarVis 2.0 |
| Onvif | Onvif Profile S | Mobile App | AntarView Pro |
| Max. Online Users | 5 | Platform | Mac OS/ Windows/iOS/Android |


General

| | | | |
|---------------------|-------------------------------|--------------------|-------------|
| Working Temperature | -30°C~+60°C | Ingress Protection | IP67 |
| Working Humidity | 10~90% | Dimensions | Φ102*93.2mm |
| Power Supply | PoE, IEEE802.3af DC12V±10% | Net Weight | 0.50KG |
| Power Consumption | < 3W | Gross Weight | 0.70KG |

Ordering Information

| Type | Part Number | Description |
|------------|-------------|-----------------------------------|
| 8MP Camera | DL-858M28B | 8MP Network Camera(3.6~11mm Lens) |

Dimensions (mm)



www.zkteco.com

