

X 628-C **3-inch Fingerprint** Time& Attendance Terminal



The firmware of X628-C has been upgraded to the New Firmware. It brings many new experiences, including the new stunning GUI, rock-solid stability, faster matching speed and better expanded lity.

Users can easily manage data by networking X628-C via RS232, TCP/IP, and USB-host. Most importantly, all the functions can still operate in a networking state. X628-C is compatibility with various types of USB flash disks, ADMS and former SDK. It also supports data backup and retrieve to avoid the risk of accidental deletion.

It promotes the fingerprint time & attendance management to the next level. You can get the best of benefits from the X628-C.

Feture

Remarkable user experience

- Intuitive and stunning UI designed with the most popular and internationalized factor.
- Interface operation adopts modularized hierarchical design. Simpler, Better and More logical.
- Faster matching speed: less than 0.5 second.

Excellent expandability

 Easy to extend functions and customize customers' demand.

Enhanced features and performance

- User validity settings.
- Data backup and retrieve.
- Advanced User ID consisted of letters and numbers.
- Chip encryption for firmware protection.
- More flexible menu configuration: double line text display.
- Built-in Serial and Ethernet ports

Specifications

| Fingerprint Capacity | 3000 |
|----------------------|---|
| Card Capacity | 10,000 (Optional) |
| Record Capacity | 100,000 |
| Display | 3-inch Screen |
| Communication | RS232, TCP/IP, USB-host, WiFi |
| Standard Functions | Workcode, SMS, DST, Scheduled-bell, Self-Service Query, Automatic Status Switch |
| | 9 digit user ID |
| Optional Functions | Photo ID, ADMS, ID/Mifare/HID, Webserver, External Printer and Bell, WiFi, Multiple Verify Mode |
| Software | ZKTime. Net, BioTime 8.0 |
| Power Supply | DC 5V 0.8A |
| Verification Speed | ≤1 Sec. |
| Operating Temp. | 0°C- 45 ℃ |
| Operating Humidity | 20%-80% |
| Dimension | 190 \times 135.8 \times 51.5mm (Length \times Width \times Thickness) |
| Net Weight | 0.9 kg |

Configuration





ZKTeco Inc.

ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129 Tel: 86-755-8960 2345/46/47/48

Global Offices:

USA: + 1 732-412-6007 EU: +34 916532891 Brazil: +55 31 2515-8326 Thailand: +66-027199154 Mexico: +52-55-52928418 South Africa: +27 12 259 1047 Egypt: +201110444134 Dubai: +971 4 6091 310 India: +91 8123536788 Indonesia: +62 21 2921 8949 Vietnam : +84-0169-5813007 Philippines: +63 9084118832 Russia: +8 915 178-46-81



ZKTECO CO.,LTD.

V1.0 2019.11 25