

ZKP8001

Thermal Receipt Printer



Features

- Low noise and high-speed printing;
- Support cash drawer driver;
- Easy for paper installation, Easy maintenance and excellent structure;
- Low power consumption and low operating costs (No Ribbons or Ink cartridges);
- Built-in data buffers (capable of receiving print data while printing);
- Characters can be amplified, printed in bold optionally, and line spacing printing can be adjusted;
- Support different density bitmap graphics printing;
- Support NV image downloading and printing;
- High-speed printing using embedded soft font for all interfaces;
- Compatible with ESC/POS print instruction set, optional columns and font(adjusted by DIP switch);

Model		ZKP8001
Printing	Print Method	Direct Thermal Line Printing
	Print Speed	300mm/sec
	Print Command	Compatible with ESC/POS
	TPH	100 km
Interface	Optional	Serial/USB/Ethernet/Bluetooth/WIFI
Character	Font A	12*24dots,1.5(W)*3.0(H)mm
	Font B	9*17dots,1.1(W)*2.1(H)mm
	Chinese	24*24dots,3.0(W)*3.0(H)mm
	Alphanumeric	ASCII 12x24dots
Barcode	1D	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128
	2D	QR CODE
Power Supply	Output	DC 24V/2.5A
	Cash drawer	DC 24V/1A
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	79.5±0.5mm(Print Width 72mm)
	Paper Thickness	0.060~0.08mm
	Roll Diameter	80mm
	Paper Cutter	Auto Cutter: Full or Partial cut
Physical Environment	Temperature	0-45℃
	Contrast Humidity	10%-80%RH
	Weight	2kg
Dimension		190*145*145mm(L*W*H)
Software	Driver	Win 2000 , Win 2003 , Win XP , Win Vista , Win 7 ,Win 8 ,Win 10, Linux Compatible wit EPSON , SAMSUNG

