

BS-32E12/13B | E series

2MP Low Light IR Bullet Analog Camera



- 1/2.9" 2MP Sony COMS
- AHD/TVI/CVI/CVBS Video Output
- IR Effective Range 10~20m
- High Quality Optical Lens 3.6mm/6mm Optional
- Lightning Protection Up to 6KV
- IP67 Ingress Protection

2MP**2D
DNR****IP67**

System Overview

E series HD analog camera adopts advanced 4-in-1 ISP and 1/2.9" image sensor, featured by the excellent low light image details with wide FOV, compact design with unique 1-key installation base. It offers built-in UTC function to switch the signal output flexibly among the 4 popular technologies. It's ideal solution for SMB solution with high cost-performance ratio and simplicity for installation.

Functions

Long Distance Transmission

Powered by leading HD Videoloss technology, it supports up to 500m/800m transmission over RG59/RG6 coaxial cables separately.

Smart IR

E series is designed with smart IR function to avoid of the IR LED overexposure when object/people is getting closer to the camera in the night, ensuring the light intensity is changing proportionally with the distance between camera and objects.

Advanced 4 in 1 technology

E series is built in with advanced 4 in 1 technology, it's equipped with UTC chipset on board which could support to adjust HD analog signal output flexibly, such as AHD/TVI/CVI/CVBS. It's the final solution for true plug-n-play to work with any brand of HD analog DVR seamlessly.

Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank.

Support $\pm 30\%$ input voltage tolerance, it could work safely in extreme unstable power condition.

With working temperature range -30°C to $+60^{\circ}\text{C}$, it works well in a variety of harsh outdoor environments.

Technical Parameters

Camera

Model	BS-32E12B	BS-32E13B	Effective Pixels	1920(H)*1080(V)
Image Sensor	1/2.9" 2MP Sony COMS		S/N Ratio	More than 52dB
Scanning System	Progressive		IR Distance	10~20m
Min. Illumination	0.01Lux/F2.0(color) 0 Lux with IR		IR LED No	1

Lens

Focal Length	3.6mm	6mm	FOV	85°	56°
Aperture	F2.0				

Video

Video Output	AHD/TVI/CVI/CVBS	AGC	Supported
Resolution	25/30fps@1080P	Day/Night	Auto(ICR)/Manual
OSD Menu	Supported	White Balance	Supported
BLC	Supported	Noise Reduction	2D DNR
WDR	DWDR		

General

Working Temperature	-30℃~+60℃	Ingress Protection	IP67
Working Humidity	10~90%	Dimensions	145 (L)*65 (W)*65(H)mm
Power Supply	DC12V±10%	Net Weight	0.26KG
Power Consumption	<3.2W(IR cut off)	Gross Weight	0.37KG

Certifications

CE	EN55032, EN55024, EN61000-3-2, EN61000-3-3	FCC	Part 15 Subpart B, ANSI C63.4-2014
----	--	-----	------------------------------------

Ordering Information

Type	Part Number	Description
2MP Camera	BS-32E12B	2MP Analog Camera(3.6mm Lens)
	BS-32E13B	2MP Analog Camera(6mm Lens)

Dimensions (mm)

