

# ES-31A11B | EZ series

720P IR Eyeball Analog Camera



- · 1/4" 720P CMOS
- · AHD/TVI/CVI Video Output
- · IR Effective Range 10~20m
- · High Quality Optical Lens 2.8mm
- · IP67 Ingress Protection









## **System Overview**

EZ Series 720P HD analog camera adopts advanced 3-in-1 ISP and 1/4 Image sensor, featured by the excellent image details with wide FOV. It offers built-in UTC function to switch the signal output flexibly among the 3 popular technologies. It's ideal solution for SMB solution with high cost-performance ratio and simple installation.

### **Functions**

### Long Distance Transmission

Powered by leading HD Videoloss technology, it supports up to 500m/800m transmission via RG59/RG6 coaxial cables respectively.

### Smart IR

EZ series is designed with smart IR function to avoid of the IR LED overexposure when object/people is getting closer to the camera in the night, ensuring the light intensity is changing proportionally with the distance between camera and objects.

### Advanced 3-in-1 Technology

EZ series 720P HD analog camera is built-in with advanced 3-in-1 technology, it's equipped with UTC chipset on board which could support to adjust HD analog signal output flexibly, such as AHD/TVI/CVI. It's the final solution for true plug-n-play to work with any brand of HD analog DVR seamlessly.

#### Protection

With precise mechanical and rugged casing design, it stands against water and dust with industrial IP67 rank. Support  $\pm 30\%$  input voltage tolerance, it could work safely in extreme unstable power condition. With working temperature ranging from -30°C to +60°C, it works well in a variety of harsh outdoor environments.

### **Technical Parameters**

### Camera

| Model             | ES-31A11B                               | E  |
|-------------------|---|----|
| Image Sensor      | 1/4"720P CMOS                           | 9  |
| Scanning System   | Progressive                             | -1 |
| Min. Illumination | 0.1Lux/F2.4 (color)<br>0 Lux with IR on | -1 |

| Effective Pixels | 1280(H)* 720(V) |
|------------------|-----------------|
| S/N Ratio        | More than 52dB  |
| IR Distance      | 10~20m          |
| IR LED No.       | 10              |

#### Lens

| Focal Length | 2.8mm |
|--------------|-------|
| Aperture     | F2.4  |

| FOV | 63° |
|-----|-----|
|-----|-----|

#### Video

| Video Output | AHD/TVI/CVI   |
|--------------|---------------|
| Resolution   | 25/30fps@720P |
| OSD Menu     | Supported     |
| BLC          | N/A           |
| WDR          | DWDR          |

| AGC             |     | Supported        |  |
|-----------------|-----|------------------|--|
| Day/Night       | _0, | Auto(ICR)/Manual |  |
| White Balance   | 10  | Supported        |  |
| Noise Reduction |     | 2D DNR           |  |

### General

| Working Temperature | -30°C~+60°C   |
|---------------------|---------------|
| Working Humidity    | 10~90%        |
| Power Supply        | DC12V±10%     |
| Power Consumption   | <3.2W(IR off) |

| Dimensions   | Ф85.65х95mm |
|--------------|-------------|
| Net Weight   | 0.25KG      |
| Gross Weight | 0.28KG      |

### **Ordering Information**

| Туре        | Part Number | Description                    |
|-------------|-------------|--------------------------------|
| 720P Camera | ES-31A11B   | 720P Analog Camera(2.8mm Lens) |

### Dimensions (mm)



