

ProFAC

Face & RFID Access Control Terminal



ProFAC is an access control terminal with RFID and face detection capability. With ZKTeco's latest ZKFACE version 7.0 high-speed face recognition algorithm and ZMM220 hardware platform (1.2GHZ clock rate), it has extremely high verification speed and low error rate. The ProFAC can hold up to 2000(1:N) facial templates, 4000 (1:1) facial templates, and 10,000 RFID cards. It is compatible with third party controllers and devices like electric door locks, alarms, door bells, and door sensors.

Features



Advanced Face Recognition Technology



Built In Camera
* Event Snapshot
* User Photo



Simple Management & Scalability



TFT-LCD Color Touch Screen



Multiple Verification Modes:
Face/ Card / Password



Specifications (G: GL Exclusive Feature)

Capacity

Faces	2,000 (1:N) / 4,000 (1:1)
Cards	10,000
Transactions	100,000
User Photos	4,000
Event Photos	2,000

Communication

- G TCP / IP
- USB Host
- Wiegand Input / Output
- Security Relay Box

Access Control Interface

Lock Relay Output
Alarm Output / Auxiliary Input
Exit Button / Door Sensor
Doorbell Output

Hardware

- G 1.2GHz High Speed CPU
- G Memory 128MB RAM / 256MB Flash
- G 2.8 Inches TFT-LCD Touch Screen
- 125KHz EM Reader / IC Card (Optional)
- Hi-Fi Voice & Indicator
- Tamper Switch Alarm
- G Dual IR Camera

Standard Functions

Access Levels / Groups / Holidays
DST / Bell Schedule
Duress Mode (Password)
Anti-Passback
Record Query
Custom Wallpaper & Screen Saver

Special Functions

- G Multiple Verification Modes
- G Event Snapshot
- User Photo
- ZK Encrypted Card (Optional)

Compatibility

Wiegand Slave Reader
ZKBioSecurity Software


Additional Info

Working Temperature: -10 °C ~ 50 °C
Dimensions: 190.5 × 85 × 103 mm.
ZKFace v7.0 Algorithm
Face: FAR≤0.001% FRR≤1%
Package Includes 12V 3A Power Supply

Power

Operating Voltage 12V DC
Current Draw < 500mA

Configuration



Dimensions (mm)

