

## **ZKB201**

## 2D Barcode Scanner



ZKB201 is an economical two-dimensional scanning scanner with simple integration, stable performance, and fast scanning speed. It also supports manual trigger and automatic continuous scanning mode.

Advanced CMOS image recognition technology, intelligent image recognition system, and patent lighting technology are applied. Therefore, the scanner can read all kinds of one-dimensional and two-dimensional barcodes in high-speed and all-around way.

## **Features**

- · Plug and play without driver installation;
- Direct transmission of information of multi-language barcodes;
- · Adopt 32-bit master chip and patented software;
- Maintain long-term sensitivity.

## **Specifications**

| General                       |  |
|-------------------------------|--|
| Weight                        | 160g (without wire)  |
| Dimensions (L×W×H)            | 175mm×72mm×100mm   |
| N 2                           |  |
| Wire length                   | 1.8m   |
| Interface type                | Standard USB (Full Speed ,USB 2.0)   |
| Material                      | ABS+PC   |
| Color                         | Black  |
| User indicators               | LED, buzzer  |
| Scanning Performance          |  |
| Light source                  | Lighting: white LED; Focusing: Green LED; Wavelength: 525nm  |
| Image sensor                  | 640×480 CMOS   |
| Processor                     | ARM32-bit  |
| Startup time                  | 4s   |
| Analytical ability            | 1D: ≥5mil; 2D: ≥8.7mil @PCS90%   |
| Depth of focus                | 5mil: 50~130mm;13mil: 50~270mm   |
| Scanning mode                 | Manual scanning, automatic scanning  |
| Reading angle                 | Roll: ±360°; Pitch: ±60° (or greater); Yaw: ±70° (or greater)  |
| Field of view                 | Horizontal 40°, Vertical 30°   |
| Motion tolerance              | 2.3m/s   |
| Input power                   | 160mA @ 5V DC  |
| Light levels                  | 70000Lux   |
| Decode capabilities           | 1D: Codabar, Code39, Code32, Interleaved 2 of 5 (ITF25), Industrial 2 of 5, Matrix 2 of 5, Code93, Code11, Code128, Gs1-128, UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, ISBN, ISSN, GS1 databar, GS1 databar limited, GS1 databar expanded 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec |
| Environmental                 |  |
| Operating temperature         | -20°C to 55°C  |
| Storage temperature           | -20°C to 60°C  |
| Relative humidity             | 5% to 95% (non-condensing)   |
| Protection level              | IP54   |
| Drop Test                     | 1.8m, 100times   |
| High and low temperature test | Work properly for 30 minutes under simulation of temperature of -20°C and 60°C   |
| Transport vibration test      | 10H@125RPM   |

