

ZKD15 Series

Touch Monitor



ZKD1502

- 15" TFT LCD Panel
- 5 wires touch screen
- 12V 3A Power Adapter

ZKD1503

- 15" AUO TFT LCD Panel
- 5 wires touch screen by Higgstec (anti-high temperature)
- 12V 3A Power adapter from TaiWan

Features

- TaiWan EETI touch card;
- Factory-control Grade A LED panel;
- 24-hour non-stop operation;
- Efficient heat dissipation system;
- Foldable Touch Monitor;
- Support windows platforms;
- Multiple installation methods available, including horizontal, vertical and VESA standard;
- High gloss black edges;
- Integrated touch function and LCD solution;
- Support USB touch interface;
- Support VGA input format.

Specifications

Model	ZKD1502	ZKD1503	
LCD Type	Type	15" TFT LCD Panel	15" AUO TFT LCD Panel
	Dimension	350*44*275mm (L*W*H)	
	Display Area	305x230 (mm)	
	Max Resolution	1024x768 @ 60Hz	
	Color	16.7 million	
	Brightness	250cd/m2	
	Response Time	5ms	
	Visual Angle (Typ.at CR > 10)	Horizontal (left/right):85°/85° Vertical (upper/lower):V80°/80°	
	Contrast Ratio	1000:1	
	Video Input Format	VGA	
	Frequency (H/V)	30~80KHz / 60~75Hz	
	MTBF	50,000 hours	
	LED Backlight Lifespan	50,000 hours	
Touch Panel	Type	ZKD1502R: 5 wires resistive touch (Standard) ZKD1502C: 5 wires capacitive touch (Optional)	ZKD1503R: 5 wires resistive touch from TaiWan Higgstec (anti-high temperature) (Standard) ZKD1503C: 5 wires capacitive touch from TaiWan Higgstec (anti-high temperature) (Optional)
	Interface	USB	
	Response Time	USB: 10 ms	
Power Supply	Type	External power adapter	
	Power Adapter	12V 3A Power adapter	12V 3A Power adapter from TaiWan
	Input Voltage	100-240 VAC, 50-60 Hz	
	Output Voltage	12 volts at 4 amps max	
	Power Consumption	12W(Max)	
Work Environment	Operating Temp.	0°C~50°C	
	Storage Temp.	-20°C~60°C	
	Operating Humidity	5%~90%	
	Storage Humidity	5%~90%	
Appearance	Installation Mode	1) VESA 75 mm 2) Using a horizontal or vertical mounting support	
OSD Control	Button	AUTO, +, POWER, -, MENU	
	Function	Brightness, Contrast, Auto correction, Phase, Clock, Row and column position, Language, Function setting, Reset	
Other	Accessory	Power cable; Power adapter; USB cable; VGA cable	
	Warranty Period	1 year	

